

# QuadroClad™

G L A S S   R A I N S C R E E N   S Y S T E M S





## QuadroClad Glass Product Data

### SYSTEM OVERVIEW:

- Flat glass according to ASTM C1036.
- Heat strengthened or tempered glass according to ASTM C1048.
- Laminated architectural glass according to ASTM C1172.
- Safety glass according to ANSI Z97.1-2004. (Upon request)
- Non-progressive installation.

<b>WIDTH (max)</b>	6 ft (1830 mm)	
<b>LENGTH (max)</b>	12 ft (3650 mm)	
<b>GLASS PANE THICKNESS</b>	0.25 in (6 mm), 0.3125 in (8 mm), 0.375 in (10 mm)	Other thickness available upon request.
<b>SYSTEM WEIGHT</b>	5.5 lbs / sq. ft (26.86 kg / sq. m)	Weight will vary depending on Glass pane thickness
<b>MAX SIZE IN COMBINATION</b>	Dependent on system type and configuration.	
<b>JOINT WIDTH</b>	0.375 in (10 mm), 0.5625 in (15 mm)	
<b>COATING</b>	Color matched Ceramic Frit	
<b>GLASS PANE TYPES</b>	Low Iron (Colorless glass) or Clear Float (Green edge - Standard)	
<b>COLORS</b>	Custom color capabilities including solid, semi-translucent, or translucent possibilities. All colors UV stable and chemical resistant.	









Terracotta



Aluminum



Glass



Specialty Solutions